

WINDOW TYPE INVERTER

koppel

FULL DC INVERTER

up to **60%**
Energy Savings



1.0HP & 1.5HP



2.0HP & 2.5HP

COMPACT MODEL



R32
REFRIGERANT



GOLD
FINS



SILVER ION
ANTIBACTERIAL FILTER



SLEEP
MODE



SELF
DIAGNOSIS



AUTO
RESTART

Model	Remote	KV09WR-ARF31A	KV12WR-ARF31A	KV18WR-ARF31A2	KV24WR-ARF31A2
	HP	1.0	1.5	2.0	2.5
Cooling Capacity	BTU/Hr	9,450	11,800	18,300	22,100
	kJ/Hr	9,970	12,449	19,307	23,316
Power Supply	V/Ph/Hz	230~/60	230~/60	230~/60	230~/60
Rated Power	W	742	1,178	1,560	1,840
Rated Current	A	4.17	5.27	6.16	8.20
EER	BTU/W-Hr	12.74	10.02	11.73	12.01
	kJ/W-Hr	13.44	10.57	12.38	12.67
CSPF		4.25	4.55	5.14	5.17
Star Rating		★★★★★	★★★★★	★★★★★	★★★★★
Refrigerant		R32	R32	R32	R32
Operation Temperature (Min-Max)	°C	17-32	17-32	17-32	17-32
Applicable Area (Unloaded Space)	SQM	9-17	12-21	24-35	28-41
Airflow Volume (Hi/Mi/Low)	CMH	353/310/269	374/330/270	771/677/587	763/676/612
Noise Level (Hi/Mi/Low)	dB(A)	51.8/49.2/46.8	53.5/51/46.5	54.7/51.7/48.3	56.4/53.6/50.8
Unit Dimension (WxDxH)	mm	450.6x675x350	450.6x675x350	660x780x428	660x780x428
Packaging Dimension (WxDxH)	mm	530x743x435	530x743x435	770x915x510	770x915x510
Unit Weight (Net/Gross)	Kg	30.6/33.1	31.7/34.3	52.3/56.8	53/57.4

NOTES:

- (1) Testing Conditions: Indoor air inlet temperature: 27°C DB / 19 °C WB; Outdoor air inlet temperature: 35°C DB / 24°C WB.
 (2) Specifications are subject to change without prior notice for continuous product improvement.
 (3) Koppel is a registered trademark of Koppel Inc.

CEBU

CEBU Door 1-2, NSB Bldg.
A. Cortez Avenue, Mandaue City
Tel. No.: (032) 346-7278
Fax No.: (032) 346-7279

ILOILO

Door 8-10, NSB Bldg.,
Rizal Street, Lapuz, Iloilo City
Tel. No.: (033) 330-2926

CAGAYAN DE ORO

CDO 78-78 Warehouse 1,
Zone 5, Cugman
National Highway,
Cagayan de Oro City
Tel. No.: (088) 880-6326

DAVAO

Buhangin Rd. corner Ladislawa Ave.
Davao City
Tel. No.: (082) 308-10403