

WINDOW TYPE

koppel

evo series



R32
REFRIGERANT



GOLD
FINS



SILVER ION
ANTIBACTERIAL FILTER



*TIMER



*SELF
DIAGNOSIS



*AUTO
RESTART

Model	Manual Remote	KWR-06M4A2 KWR-06R4A2	KWR-07M4A2	KWR-09M4A2 KWR-09R4A2	KWR-12M4A2 KWR-12R4A2	KWR-18R4A2
Cooling Capacity	HP	0.6	0.75	1.0	1.5	2.0
	BTU/Hr	6,135	7,350	9,000	12,300	19,200
	kJ/Hr	6,472	7,754	9,495	12,977	20,256
Power Supply	V/Ph/Hz	230~/60	230~/60	230~/60	230~/60	230~/60
Rated Power	W	575	690	840	1,160	1,740
Rated Current	A	2.5	3.1	3.8	5.2	7.9
EER	BTU/W-Hr	10.67	10.7	10.7	10.6	11.0
	kJ/W-Hr	11.26	11.2	11.3	11.2	11.6
CSPF		3.32	3.32	3.33	3.3	3.43
Star Rating		★★	★★	★★	★★	★★★
Refrigerant		R32	R32	R32	R32	R32
Operation Temperature (Min-Max)	°C	17-30	17-30	17-30	17-30	17-30
Applicable Area (Unloaded Space)	SQM	7-11	9-14	12-18	16-23	23-34
Airflow Volume (Hi)	CMH	233	366	340	434	780
Noise Level (Low)	dB(A)	53	45	46	54	52
Unit Dimension (WxDxH)	mm	406x335x306	450x535x346	450x535x346	450x585x346	660x680x428
Packaging Dimension (WxDxH)	mm	455x390x380	495x580x435	495x580x435	505x640x435	746x815x515
Unit Weight (Net/Gross)	Kg	16.9/18.2	24.6/27	25.5/28.2	31.8/34.4	53.1/57.8

NOTES:

(1) The above data was based on cooling conditions: Indoor air temp. 27°C DB / 19°C WB; Outdoor air inlet temperature: 35°C DB / 27°C WB.

(2) Specifications are subject to change without prior notice for continuous product improvement.

(3) Koppel is a registered trademark of Koppel Inc.

*Applicable to Remote Models only.

CORPORATE OFFICE & PARTS SALES CENTER

Hyatt Centre, Ortigas Avenue,
Brgy. Wack-Wack, Mandaluyong City
Tel. No.: (02) 8823-8883 Loc. 316 to 322

MANUFACTURING PLANT

Industry Drive, Carmelray Industrial Park 1,
Canlubang, Calamba City, Laguna
Tel. No.:(02) 8823-8883

VILLONGCO

Brgy. BF Homes, Villongco,
Parañaque, Corner
1720 Metro Manila

TARLAC

Unit 2, Block 1 Lot 10,
Brgy. San Jose,
Tarlac City