

Ceiling Concealed Split Ducted



**HIGHLY EFFICIENT
FAN MOTOR**



**HEAVY
DUTY**



**RUST
PROOF**

A. AIR HANDLING UNIT MODEL		KSCC-12	KSCC-18	KSCC-24	KSCC-36
Nominal Cooling Capacity	BTU/h	12,000	18,000	24,000	36,000
	kJ/h	12,660	18,990	25,320	37,980
Nominal Airflow	CFM/CMH	600/1,020	700/1,190	800/1,360	1,200/2,040
Motor	HP	1/10	1/10	1/10	1/4
Cabinet Dimension	mm				
Height		261	261	261	330
Width		1,000	1,000	1,000	1,100
Depth		513	513	513	555
Operating Weight	Kg	31	33	34	47
External Static Pressure	Pa	30	30	30	40
B. CONDENSING UNIT MODEL		KPC-12IH0	KPC-18IH0	KPC-24IH0S	KPC-36IH0
Motor	HP	1/20	1/8	1/8	1/4
Volts, Hz, Ph		230/60/1	230/60/1	230/60/1	230/60/1
Compressor Type		Rotary	Rotary	Reciprocating	Reciprocating
Power Input ACCU	Kw	1.38	2.17	2.63	3.76
Cabinet Dimension	mm				
Height		520	636	636	812
Width		745	840	840	1,016
Depth		250	310	310	355
Operating Weight	Kg	35	57	62	88
Pipe Size	Liquid/Gas	6/13	10/16	10/16	10/19

Note:

(1) Specifications are subject to change without prior notice for continuous product improvement.