

# Window Type ERA Series



ULTRA HIGH EFFICIENCY



ECO-FRIENDLY R410A REFRIGERANT



ENERGY SAVINGS



ANTI-BACTERIAL FILTER

	Manual Remote	KWR-06M5A	KWR-09M5A KWR-09R5A	KWR-12M5A KWR-12R5A	KWR-18M5A KWR-18R5A	KWR-24R5A
Cooling	Btu/h	5,400	9,573	12,000	18,000	23,223
	Kj/h	5,697	10,100	12,660	18,990	24,500
Capacity	HP	0.6	1.0	1.5	2.0	2.5
Input	W	545	960	1,152	1,730	2,350
Rated Current	A	2.3	4.1	5.5	8.7	10.3
EER	Kj/h-W	10.4	10.5	11.0	11.0	10.4
Max. input consumption	W	600	1,200	1,480	2,150	3,000
Voltage, Frequency, Phase	V~, Hz, Ph	220-230V~60Hz,1Ph	220-230V~60Hz,1Ph	220-230V~60Hz,1Ph	220-230V~60Hz,1Ph	220-230V~60Hz,1Ph
Indoor Airflow	m <sup>3</sup> /h	230	400	490	700	800
Indoor Noise Level	dB(A)	58	52-55	50-55	55-59	50-55
Unit Dimension WxDxH	mm	410x344x300	456x557x345	610x565x385	660x690x435	660x780x435
Carton Dimension WxDxH	mm	480x400x380	494x607x435	700x625x440	740x770x512	740x860x512
Weight Net/Gross	Kg	18/20	29/32	36/39	36/39	61/66
Operation Temperature	°C	16-32	16-32	16-32	16-32	16-32
Applicable Area	m <sup>2</sup>	7-10	13-17	18-24	25-33	33-44

**NOTES:**

(1) Testing Conditions: Indoor air inlet temperature: 27° DB / 19 degrees WB; Outdoor air inlet temperature: 35° DB / 27° WB.

(2) Specifications are subject to change without prior notice for continuous product improvement.

(3) Koppel is a registered trademark of Koppel, Inc.

**Head Office:**  
Industry Drive, Carmelray  
Industrial Park 1,  
Canlubang Laguna  
Tel.: (02) 8.823.8883

**Customer Service Parts Sales**  
G/F Hyatt Centre, Ortigas Ave.,  
Brgy. Wack-Wack,  
Mandaluyong City  
Tel. No.: (02) 8.823.8883  
Local: 316 - 322

**Davao**  
J.P. Cabaguio Ave.,  
Davao City  
Tel. No.: (082) 221.6419  
Fax No.: (082) 221.6418

**Cebu**  
Door 1&2 Rozen Bldg.,  
A. Cortez Avenue,  
Mandaue City  
Tel. No.: (032) 346.7278  
Fax No.: (032) 346.7279

**Agayon De Oro**  
CDO 78-78 Warehouse,  
Warehouse 1, Zone 5, Cugman  
National highway, CDO  
Tel. No.: (088) 880.6326

**Iloilo**  
Door 8 and 9 NSB Bldg.  
Rizal Street, Lapuz, Iloilo City  
Tel. No.: (033) 330.2926