

Window Type ERA Series



ENERGY SAVINGS



AUTO PROTECTION



GOLD FINS



***24HR TIMER**



3-IN-1 FILTER



ULTRA HIGH EFFICIENCY



***SLEEP MODE**

Model	Manual Remote	KWR-09M5A KWR-09R5A	KWR-12M5A KWR-12R5A	KWR-18M5A KWR-18R5A	KWR-24R5A
Cooling Capacity	HP	1.0	1.5	2.0	2.5
	Btu/h	9,573	12,000	18,000	23,223
	kJ/hr	10,100	12,660	18,990	24,500
Power Supply	V/Hz/Ph	230/60/1	230/60/1	230/60/1	230/60/1
Rated Power	W	960	1,152	1,730	2,350
Rated Current	A	4.1	5.5	8.7	10.3
EER	Btu/h-W	10.0	10.4	10.4	9.9
	kJ/hr-W	10.5	11.0	11.0	10.4
Refrigerant		R410A	R410A	R410A	R410A
Operation Temperature (Min-Max)	°C	18-31	18-31	18-31	18-31
Applicable Area (Unloaded Space)	m ²	13-17	18-24	25-33	33-44
Airflow Volume (Hi)	m ³ /h	400	490	700	800
Noise Level (Low)	dB(A)	58	50	55	50
Unit Dimension (WxDxH)	mm	456×557×345	610×565×385	660×690×435	660×780×435
Packaging Dimension (WxDxH)	mm	494×607×435	700×625×440	740×770×512	740×860×512
Unit Weight (Net/Gross)	Kg	29/32	36/39	36/39	61/66

NOTES:
 (1) Testing Conditions: Indoor air inlet temperature: 27° DB / 19° WB; Outdoor air inlet temperature: 35° DB / 27° WB.
 (2) Specifications are subject to change without prior notice for continuous product improvement.
 (3) Koppel is a registered trademark of Koppel, Inc.
 *Applicable for Remote Model only.

Head Office & Manufacturing Plant
 Industry Drive, Carmelray Industrial Park 1,
 Canlubang, Calamba City, Laguna
 Tel. No.: (02) 8823-8883

Customer Service & Parts Sales Center
 G/F Hyatt Centre, Ortigas Avenue,
 Brgy. Wack-wack, Mandaluyong City
 Tel. No.: (02) 8823-8883
 Loc. 316 to 322

Davao
 J.P. Cabaguio Avenue, Davao City
 Tel. No.: (082) 221-6419
 Fax No.: (082) 221-6418

Cebu
 Door 1&2 Rozen Bldg.
 A. Cortez Avenue, Mandaue City
 Tel. No.: (032) 346-7278
 Fax No.: (032) 346-7279

Cagayan de Oro
 Whse 1-7878 Ravago Bldg.,
 Cugman Highway,
 Cagayan de Oro City
 Tel. No.: (088) 880-6326

Iloilo
 Door 8 and 9 NSB Bldg.
 Rizal Street, Lapuz, Iloilo City
 Tel. No.: (033) 330-2926